

Item no.: 387848

EDS-308-MM-ST-T - Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports

from **447,79 EUR**

Item no.: 387848
shipping weight: 0.80 kg
Manufacturer: MOXA



Product Description

Moxa has a large portfolio of industrial unmanaged switches that have been specifically designed for industrial Ethernet infrastructure. Our unmanaged Ethernet switches uphold the stringent standards that are required for operational reliability in harsh environments. EDS-308-MM-ST-TEDS-308 Series Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connector, -40 to 75°C operating temperature Input/Output Interface Alarm Contact Channels- 1 relay output with current carrying capacity of 1 A @ 24 VDC Ethernet Interface 10/100BaseT(X) Ports (RJ45 connector)- 6- Auto negotiation speed- Full/Half duplex mode- Auto MDI/MDI-X connection 100BaseFX Ports (multi-mode ST connector)- 2 Standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control DIP Switch Configuration Ethernet Interface- Port break alarm Switch Properties MAC Table Size- 2 kbits Packet Buffer Size- 768 K Processing Type- Store and Forward Power Parameters Input Current- 0.15 A @ 24 VDC Connection- 1 removable 6-contact terminal block(s) Operating Voltage- 9.6 to 60 VDC Input Voltage- Redundant dual inputs- 12/24/48 VDC Reverse Polarity Protection- Supported Overload Current Protection- Supported Physical Characteristics Housing- Metal IP Rating- IP30 Dimensions- 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in) Weight- 790 g (1.75 lb) Installation- DIN-rail mounting- Wall mounting (with optional kit) Environmental Limits Operating Temperature- -40 to 75°C (-40 to 167°F) Storage Temperature (package included)- -40 to 85°C (-40 to 185°F) Ambient Relative Humidity- 5 to 95% (non-condensing) Standards and Certifications Safety- UL 508- UL 60950-1- CSA C22.2 No. 60950-1- EN 62368 (LVD) EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 MHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V Hazardous Locations- ATEX- Class I Division 2 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Freefall- IEC 60068-2-32 Maritime- DNVMTBFTIME- 2,382,553 hrs Standards- MIL-HDBK-217F

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

