

Item no.: 391418

RG-RAP6262 - Reyee access point

from **168,15 EUR**

Item no.: 391418
 shipping weight: 4.70 kg
 Manufacturer: Ruijie Networks



Product Description

Product Description RG-RAP6262 is one of Ruijie Networks' fully developed Wireless Wi-Fi 6 Omnidirectional Access Points with roaming support for seamless transition between individual APs. The device is equipped with a Gigabit Ethernet port with support for 802.3at PoE power, a Gigabit SFP optical port for connections up to 20km away and a dual band Wi-Fi 6 MU-MIMO radio with modulation speeds of 576Mbps in the 2.4GHz and 2402Mbps in the 5GHz band using a 160MHz wide channel. The innovative UFO design allows for easy installation in high places. Key benefits- Easily expandable WLAN with Reyee Mesh- SFP interface- Supports MU-MIMO, roaming, beamforming, OFDMA and other technologies- High throughput thanks to WiFi 6- Outdoor design, IP68 protection- Dual-band data transmission- Management via Ruijie Reyee Cloud or web interface Scope of delivery- Device- Mounting bracket- Screws- (2) metal straps Technical parameters Wireless features- Wireless frequency: 2.4 + 5 GHz (dual band) - WiFi standards: 802.11ax, 802.11ac, 802.11c - wave2, 802.11n, 802.11a, 802.11b/g - MU-MIMO: Yes- Transmission speed - 5GHz [Mb/s]: 2402 - Transmission speed - 2.4GHz [Mb/s]: 574 - Tx power 2.4GHz [dBm]: 29 - Tx power 5GHz [dBm]: 30 - Security: WPA-PSK/WPA2-PSK - 2.4GHz MIMO: 2 x 2 - 5GHz MIMO: 2 x 2 - Type of antenna: Built-in - Internal antennas: 5 - Roaming: Yes - Antenna gain [dBi]: 3, 4 Connectors and Interfaces- LAN speed: (1) 10/100/1000Mbps - Gigabit LAN: Yes - Optical interfaces: (1) 1000Mbps Power- Power over Ethernet: 802.3at - PoE type: PoE-In (only) - Max. power consumption [W]: 24 - Power via connector/terminal: 12V / 2A Physical characteristics- Protection class: IP68 - Purpose: Outdoor - Buttons: Reset - Operating temperature [°C]: -30 up to 65 - Weight [g]: 1400 - Width [mm]: 230 - Height [mm]: 195 - Depth [mm]: 230 Software- Operating mode: Access Point - Default IP address: Dynamic from DHCP, 10.44.77.253 - Default login and password: Is set by the user at the first startup

Specifications

Scan this QR code to
 view the product

All details, up-to-date
 prices and availability

