

Item no.: 385343

MGATE EIP3270 - 2-port EtherNet/IP to DF1 gateway, operating temperature 0 to 60 °C

from **510,77 EUR**

Item no.: 385343
 shipping weight: 0.40 kg
 Manufacturer: MOXA



Product Description

EtherNet/IP gateways
 The Ethernet/IP gateways from Moxa enable various communication protocol conversions in an EtherNet/IP network.
 2-Port EtherNet/IP to DF1 gateway, 0 to 60°C operating temperature
 Ethernet interface- 10/100BaseT(X) ports (RJ45 connector): 2 Auto MDI/MDI-X connector
 Ethernet software functions- Industrial protocols: Ethernet/IP (PCCC)- Configuration options:MGate ManagerTelnet console- Management:ARPDHCP clientSNMPv1TCP/IPTelnetUDP- MIB:RFC1213, RFC1317
 Serial interface- Nos. Ports: 2- Connector: 2 x DB9 male- Serial standards:RS-232RS-422- Baud rate: 1200 bps to 921.6 kbps- Data bits: 8- Parity:NoneEvenOddStop bits: 1, 2- Flow control:RTS/CTS/DTR/DSR (RS-232 only)Serial signals- RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND- RS-422: Tx+, Tx-, Rx+, Rx-, GND
 Serial software functions- Industry protocols: DF1DF1 (Transparent)- Mode: Full duplex- Max. Number of client connections: 8
 Performance parameters- Input voltage: 12 to 48 VDC- Input current: 435 mA @ 12 VDC
 Relay- Rated contact current: Resistance load: 1 A @ 30 VDC
 Physical properties- Housing: Plastic top cover, metal base plate- Protection class: IP30- Dimensions (with ears): 29 x 89.2 x 124.5 mm (1.14 x 3.51 x 4.90 in)- Dimensions (without ears): 29 x 89.2 x 118.5 mm (1.14 x 3.51 x 4.67 in)- Weight: 380 g (0.84 lb)84 lb)Environmental conditions- Operating temperature: 0 to 60°C (32 to 140°F)- Storage temperature (in packaging): -40 to 85°C (-40 to 185°F)- Relative humidity:5 to 95% (non-condensing)Standards and certifications- EMC: EN 55032/35- EMI: CISPR 32, FCC Part 15B Class A- EMS:IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/mIEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kVIEC 61000-4-5 Surge: Power: 4 kVIEC 61000-4-6 CS: 10 VIEC 61000-4-8 PFMFIEC 61000-4-11- Safety:IEC 60950-1UL 60950-1EN 62368-1UL 508- Hazardous areas:ATEXClass I Division 2IECEX - Free fall: IEC 60068-2-32- Shock: IEC 60068-2-27- Vibration:IEC 60068-2-6IEC 60068-2-64MTBF- Time: 1,204.573 hours- Standards: Telcordia SR332

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

