

Item no.: 387878

## EDS-P206A-4POE-MM-ST-T - Unmanaged Ethernet switch with 4 PoE ports

from **555,27 EUR**

Item no.: 387878  
shipping weight: 0.40 kg  
Manufacturer: MOXA



### Product Description

Unmanaged Switches Moxa has a large portfolio of industrial unmanaged switches specifically designed for industrial Ethernet infrastructure. Our unmanaged Ethernet switches meet the stringent standards required for operational reliability in harsh environments. Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multimode ports with ST connectors, operating temperature -40 to 75 °C Ethernet interface- 100BaseFX ports (ST multimode connector): 2- PoE ports (10/100BaseT(X), RJ45 connector): 4 Speed with auto-negotiation Full/half duplex mode Auto MDI/MDI-X connection- Standards IEEE 802.3 for 10BaseT IEEE 802.3af/at for PoE/PoE+ output IEEE 802.3x for flow control IEEE 802.3u for 100BaseT(X)- PoE Pinout: V+, V+, V-, V- for Pins 1, 2, 3, 6 (Endspan, MDI, Mode A) Switch Features- Packet Buffer Size: 768 kbits- MAC Table Size: 2 K- Processing Type: Store and Forward Power Parameter- Input Current: 5.55 A @ 24 VDC- Connection: 1 detachable 4-contact terminal block(s)- Operating Voltage: 12 to 57 VDC- Input Voltage: 12/24/48 VDC, Redundant Dual Inputs- Power Budget: Max. 120 W for total PD consumption Max. 30 W for each PoE port- Power Consumption (Max.): Max. 13.2 W at full load without PD consumption- Reverse polarity protection: Supported- Overload current protection: Supported Physical properties- Housing: Metal- IP protection class: IP30- Dimensions: 50.3 x 114 x 70 mm (1.98 x 4.53 x 2.76 in)- Weight: 375 g (0.83 lb)- Installation: DIN rail mounting Wall mounting (with optional kit) Environmental conditions- Operating temperature: -40 to 75°C (-40 to 167°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Relative humidity: 5 to 95% (non-condensing) Standards and certifications- EMI: CISPR 32, FCC Part 15B Class A- EMC: EN 55032/24- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Safety: UL 508- Shock: IEC 60068-2-27- Free fall: IEC 60068-2-31- Vibration: IEC 60068-2-6 MTBF- Time: 1,289,258 hours- Standards: Telcordia (Bellcore), GB

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

