

Item no.: 389851

Optical box 2 outputs with 55m cable

from **89,09 EUR**

Item no.: 389851
shipping weight: 10.00 kg
Manufacturer: Teledes



Product Description

Device authorised as a connection unit or termination unit for a fibre optic network. Thanks to its internal structure, it can accommodate optical cables (applications as a patch box) and an optical distributor with 2 or 4 outputs (application as a distribution box). It can be mounted using screws (for wall or junction box mounting) or using an insert for DIN rails. Main features: - The optical fibre enters the inside of the box through 5 areas (the 4 corners and the bottom). - Ideal dimensions for easy fibre optic installation and avoidance of small bending radii that can affect transmission (attenuation). - The multi-cable routing takes place at the rear, via various attachment points. A clamp on the underside provides a reinforced hold. Cable ties are also supplied if a higher level of security is required. - Can hold up to 4 splicing needles. - The integrated SC/APC adapters have a self-locking cover. - The front allows easy identification of the optical fibres by means of a colour code and the associated assignment of the corresponding housing unit. This makes it easier to later identify which optical cable leads to which housing unit. Width 94 mm Suitable for thermal splice protection Suitable for number of splice holders 2 Suitable for number of splice protectors 2 Height 34 mm Length 119 mm With splice holder yes Mounting type other

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

