

Item no.: TPA-PAF **TPA-PAF - TwistPort Adaptor for Rocket Prism 5ac and AirFiber 5X-HD**





Product Description

TPA-PAF - TwistPort Adaptor for Rocket Prism 5ac and AirFiber 5X-HD

TPA-PAF makes LTUT™ Rocket® Prism 5AC, Rocket® Prism 5AC Gen2, airFiber® 5X and airFiber® 5XHD compatible with any TwistPort™ antenna. TPA-PAF contains well protected space for GPS antenna that comes with ® Radios.

Connecting and disconnecting the radio from the TwistPort[™] adaptor is very simple and requires no tools.

- Antenna connection: TwistPort quick locking waveguide port
 Radio connection: 2x slide-on RP-SMA and 1x SMA for GPS
 Materials: Insert aluminium alloy, adaptor UV stabilized and weather resistant ABS plastic
- Flame rating: UL 94 HB
 Temperature: -40°C to +60°C (-40°F to +140°F)
 Wind survival: 160 km/h

- Weight: 0.52 kg/1.14 lbs single unit incl. package
 Dimensions: 20.4 x 13.7 x 10.2 cm single unit incl. package

Performance

- Frequency range: 5180 6400 MHz
 Polarization: Dual linear H+V
 VSWR: Max. 1.8
- Impedance: 50 Ohm

Compatible wireless platforms

- RF elements(R): Any TwistPort(TM) Antenna
 Ubiquiti Networks(R): LTU[™] Rocket, Rocket® Prism 5AC, Rocket® Prism 5AC Gen2, airFiber® 5X, airFiber® 5X-HD

Package contents

- TwistPort(TM) Adaptor
- AF5X and LTU Mount Adaptor

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

