

Item no.: LHG-XL-52-AC

## RBLHGG-5HPACD2HPND-XL - LHG-XL-52-AC - Extremely powerful dual-band backbone/CPE

from **185,04 EUR**

Item no.: LHG-XL-52-AC  
shipping weight: 3.00 kg  
Manufacturer: MikroTik



### Product Description

LHG-XL-52-AC - Extremely powerful dual-band backbone/CPE

Need a reliable and strong long-distance connection that never goes down? The new LHG XL 52 ac will provide just that with its dual-band capability. You can easily setup the 5 GHz channel as the main one with speed up to 600 Mbps and use the 2.4 GHz channel as an automatic backup connection with speed up to 260 Mbps.

The powerful 27 dBi 5 GHz/18 dBi 2.4 GHz antenna will provide connection with link distance up to 40 km. The grid design ensures protection against wind, it can withstand temperatures from -40°C to +70°C. Antenna element is built into the wireless unit – no loss on cables. This device can handle the heaviest loads thanks to the impressive quad-core CPU and 256 MB of RAM. It has a Gigabit Ethernet port, an SFP port, and it is 802.3af/at compliant – you can power it with the smart switches!

- Product code: RBLHGG-5HPacD2HPnD-XL
- Architecture: ARM 32bit
- CPU: IPQ-4018
- CPU core count: 4
- CPU nominal frequency: 716 MHz
- Dimensions: 550 x 291 mm
- License level: 3
- Operating System: RouterOS
- Size of RAM: 256 MB
- Storage size: 16 MB
- Storage type: Flash
- Tested ambient temperature: -40°C to 70°C

#### Powering

- PoE in: 802.3af/at
- PoE in input voltage: 12-57 V
- Number of DC inputs: 1 (PoE in)
- Max. power consumption: 18 W
- Max. power consumption without attachments: 16 W

#### Wireless

- AC speed: AC1200
- Wi-Fi generation: 5

#### Ethernet

- 10/100/1000 Ethernet ports: 1

#### Fiber

- SFP ports: 1

#### Other

- PCB temperature monitor: Yes
- Voltage monitor: Yes
- Mode button: Yes

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

