

Item no.: RUTX11_US

RUTX11 100400 - Next Generation LTE Cat. 6 Industrial Cellular Router, US Version

from **380,68 EUR**

Item no.: RUTX11_US
 shipping weight: 0.80 kg
 Manufacturer: Teltonika



Product Description

Teltonika RUTX11 - Next Generation LTE Cat. 6 Industrial Cellular Router, US Version

Teltonika proudly presents its latest RUTX11 router. It is the first device in Teltonika's new high-end router family. A powerful CPU, Gigabit Ethernet, the latest LTE Cat. 6 standard and 802.11ac Wave2 Wi-Fi enables highest data transmission and computing speeds for today's standards. Together with additional hardware, function and quality-of-life improvements, this router stands to be an exquisite entry point to the new RUTX family.

Standard package contains

- RUTX11 router
- US PSU
- 2x LTE antennas (swivel, SMA male)
- 2x Wi-Fi antennas (swivel, RP-SMA male)
- 1x GNSS antenna (adhesive, SMA male)
- 1x Bluetooth antenna (magnetic, RP-SMA male)
- Ethernet cable (1.5 m)
- QSG (quick start guide)
- Packaging box

Hardware Specs

- LTE Cat. 6 with speeds up to 300 Mbps
- Dual band 2.4 and 5 GHz Wi-Fi channels
- 802.11ac Wi-Fi with speeds up to 867 Mbps
- 802.11n Wi-Fi with speeds up to 300 Mbps
- 4x 1 Gbit Ethernet ports
- Quad core ARM Cortex A7 717 MHz CPU
- 256 MBytes Flash
- 256 MBytes DDR3 RAM
- Bluetooth v4.2 LE
- Low power/sleep mode, 10 mA (at) 12 V DC
- 4-pin DC connector with 1x digital input (ignition detection) and 1x digital output
- Grounding option
- 5x signal strength LEDs, 3x connection type indication LEDs, 2x Wi-Fi band activity LEDs, 1x power LED, 4x WAN connection indicator LEDs
- 2x Wi-Fi RP-SMA connectors
- 2x LTE SMA connectors
- 1x Bluetooth RP-SMA connector
- 1x 2.0 USB
- 2x external SIM holders
- 1x SIM holder removal pin

Electrical, Mechanical & Environmental Specs

- Input voltage: 9 - 50 V DC
- Operating temperature: -40°C to 75°C
- Storage temperature: -45°C to 80°C
- Operating humidity: 10% to 90% non-condensing
- Storage humidity: 5% to 95% non-condensing
- Dimensions: 115 x 95 x 44 mm

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

