

# Item no.: JVS-ND7008-PD02 JVS-ND7008-PD02 - PoE 8-Channel H.265 4K NVR, for Cameras up to 5 MP, 4 TB Hard Drive included

from 339,97 EUR Item no.: JVS-ND7008-PD02

shipping weight: 2.00 kg Manufacturer: Jovision



# Product Description

JVS-ND7008-PD02 - PoE 8-Channel H.265 4K NVR, for Cameras up to 5 MP, 4 TB Hard Drive included Jovision 8-channel Network Video Recorder for cameras up to 5 MP including a 4 TB hard drive. Key Features:

- Adopts the new Vstar GUI, easy to operate
  Supports intelligent VSMart coding, greatly reducing storage space
  Improved compatibility for hard disks, and up to 10 TB
  Supports Intelligent Detection and Human Detection

- Supports face capture, face comparison, and efficient comparison of face information
- Supports face search by face, deduplication, and precise playback
  Supports full PoE camera access, support 8x PoE + 8 non-PoE accesses (a total of 16)

#### Video and Audio

- IP Camera Input: 8-channel PoE cameras up to 5 MP + 8-channel non-PoE cameras upto 5 MP
- Audio I/O: 1-channel output RCA; Audio output support HDMI

### Display

- Interface: 1x HDMI, 1x VGA
   Resolution: HDMI: 3840x2160, 1920x1080, 2560x1440, 1440x900, 1280x1024, 1280x720, 1024x768; VGA: 1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768
- Multi-screen display: Port binding 1/4/5/6/7/8/9; Non-port bonding 1/4/5/6/7/8/9/10/11/12/13/14/15/16
   OSD: Camera name & time, recording, alarm detecting, remote connection, volume, channel number

#### Recording

- Compression: H.265/H.264
- Resolution: 10-channel 5.0 MP/4.0 MP/1080P/960P/720P
- Record mode: Manual, schedule, MD

#### Video Detection and Alarm

- Trigger events: Recording, snapshot, PTZ, voice, e-mail, client, buzzer
- Video detection: Motion detection, no video detection

### Playback and Backup

- Sync playback: 2-channel 5.0 MP/3-channel 4.0 MP/4-channel 3.0 MP
  Search mode: Time/date, schedule, motion detection
  Playback function: Day view, hour view, back step, rewind, pause, play, fast forward, slow, step, full screen, snap, sound on/off, zoom
  Backup mode: USB device/network
  USB: 2x USB 2.0

Network

- Interface: 1x RJ-45 port (10/100/1000 Mbps)
  POE interface: 8-port 100 Mbps IEEE 802.3af POE
  Network function: TCP/IP, DHCP, UDP, SMTP, NTP
  Smartphone: iPhone, Android
  Interoperability: ONVIF 2.4

Storage

- SATA: 11x SATA interface
  Capacity: Up to 10 TB

General

- Power supply: 48 V DC
  Consumption: ? 120 W (without HDD)
  Working temperature: -10°C ~ 55°C
  Working humidity: 10% ~ 90%
  Dimensions: 260 x 219 x 45 mm
  Weight: ? 1.05 kg (without HDD)

## Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

