

Item no.: 385599

CP-118U-T - Serial universal PCI card with 8 connections RS-232/422/485, -40 to 85 °C

from **342,29 EUR**

Item no.: 385599
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa's commitment to being a reliable serial connectivity provider is reflected in our long-term commitment to serial products and service availability. Our PCI Express, Universal PCI and PCI serial boards are designed for industrial applications and include models that operate reliably over a wide temperature range. 8-Port RS-232/422/485 Universal PCI Serial Board, -40 to 85°C Operating Temperature

Serial Interface Comm. Controller- MU860 (16C550C compatible) Bus- 32-bit Universal PCI Connector- DB62 socket FIFO- 128 bytes Max. number of cards per PC- 8 Number of ports- 8 Serial standards- RS-232, RS-422, RS-485 Baud rate- 50 bps to 921.6 kbps Data bits- 5, 6, 7, 8 Stop bits- 1, 1.5, 2 Parity- None, Even, Odd, Space, Mark Flow control- None, RTS/CTS, XON/XOFF Serial signals RS-232- Tx, Rx, D, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, GND RS-485-4w- Tx+, Tx-, Rx+, Rx-, GND RS-485-2w- Data+, Data-, GND

Serial software functions Windows driver- DOS, Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2/2016/2019 (x64), Windows Embedded CE 5.0/6.0, Windows XP Embedded Linux driver- Linux kernel 2.4.x, Linux kernel 2.6.x, Linux kernel 3.x, Linux kernel 4.x, Linux kernel 5.x UNIX driver- QNX 6, SCO OpenServer, UnixWare 7, Solaris 10, FreeBSD Performance parameters Input current- 20 mA @ 5 VDC Physical properties Dimensions- 82 x 135 mm (3.22 x 5.31 in) LED interface LED indicators- Built-in Tx, Rx LEDs for each port Environmental conditions Operating temperature- -40 to 85°C (-40 to 185°F) Storage temperature (in packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class B EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m Declaration Environmentally friendly product- RoHS, CRoHS, WEEE MTBF Time- 1.073,385 hours Standards- Telcordia SR332

Specifications

Scan this QR code to view the product
All details, up-to-date prices and availability

