

Item no.: EH-2200FX-ODU-L-EXT EH-2200FX-ODU-L-EXT - EtherHaul-2200FX ODU with Adapter, Tx Low



em no.: EH-2200FX-OD0-L-EXT shipping weight: 4.50 kg Manufacturer: Siklu



Product Description

Efficient 2Gbps E-band radio with extended rangeThe Siklu EH-2200FX-ODU-L-EXT1GbpsE-band FDD outdoor unit operates in the 71-76GHz frequencies and can be upgraded to 2Gbps. The unit comes with an adapter for an external antenna and has 4GbE ports: 2x copper RJ-45 + 2x optical SFP (MMF/SMF); DC and POE in and 1x POE out. The EH-2000 series offers 2Gbps full duplex capacity with extended range to accelerate deployment in urban, suburban or rural areas. The carrier-grade radio offers fibre-like performance, reliability and throughput with low CAPEX for a variety of markets: Business broadband- Video surveillance networks- GTTH - Gigabit to the home- Campus connectivity- Smart city networksRobust and future-proofThe EH-2X00 series offers wireless point-to-point Ethernet connectivity at up to 2 Gbps and full duplex, achieved only with QAM32 modulation, future-proofing your network. Operating in the interference-free 71-76/81-86 GHz band, the EH-2X00 makes it easy for providers and enterprises to expand their networks while maintaining fibre-like performance. Carrier-class performance and reliabilityHigh throughput and low latency deliver fibre-like performance. Siklu's EH-2X00 series hitless adaptive bandwidth coding and modulation, synchronised with user-configurable 8 levels of H-QoS, ensure correlated payload prioritisation for high availability. An integrated L2 switch with fibre and copper ports enables implementation in resilient topologies such as cascade or ring without the need for additional equipment. In addition, the F-Series is designed for mobile operators and ensures precise TDM synchronisation over IP/MPLS/Ethernet backhaul networks with integrated Sync. E and 1588v2. Small size, easy deployment and managementThe all-outdoor radio has a tiny footprint that facilitates site acquisition. Its light weight and small size contribute to quick and easy installation. The user-friendly web GUI manages local and remote units, and commissioning is possible from a NOC.No interference - reliable operationE-band

Specifications



