

Item no.: PA-M3-18X

WIBOX PA M3-18X - 3.3 - 3.8 GHz, 18 dBi PtP/Client Antenna

67,05 EUR

Item no.: PA-M3-18X shipping weight: 2.00 kg Manufacturer: QuWireless



Product Description

Wireless Instruments WiBOX PA M3-18X - 3.3 - 3.8 GHz, 18 dBi PtP/Client AntennaWiBOX PA M3-18HV is an X-polarity MIMO 2x2 panel antenna operating at a frequency range of: 3.3 - 3.8 GHz with 18 dBi gain. The antenna is intended for point-to-point (PtP) and point-to-multipoint (PtMP) connections as the client antenna. It can be used indoors and outdoors (IP 67). It works with WiMAX and LTE (bands 22, 42, 43) systems. The antenna is integrated into the top-quality WiBOX Medium box system. Features

- 2x 18 dBi gain
- Polarization H&V for the frequency of 3300 3800 MHz
- 2x SMA female connectors
- Big, ergonomic and voluminous WiBOX Medium enclosure for radio equipment installation
- Outdoor waterproof enclosure WiBOX Medium
 Designed for and resistant to any weather conditions
- RJ45 waterproof system
- Grounding system protecting against lighting DC ground

Systems

WLAN - 3.6 GHzWiMAX - 3.5 GHzLTE band - 22, 42, 43

Applications

- System integrationPoint-to-Point connections
- Point-to-Multipoint connections

Electrical Specifications

- Frequency: 3.3 3.8 GHzGain: 18 dBi
- VSWR: < 2.00 Beamwidth: 16°/16°
 Polarization: X
- Cross-Polar Isolation
 Front-to-Back: > 20 dB
- Separation between Connectors: > 32 dB
- Impedance: 50 ohmsMax Input Power: 50 W
- Lighting Protection: NoDC Ground: Yes

Mechanic Specifications

- Dimensions: 27.2 x 27.6 x 9.6 cm
 Weight: 2 kg
 Connector: RJ45
 Material: ABS
 Waterproof level: IP67
 Operating temperature: from -40 °C to 80 °C

Mounting Kit

- Dimensions: 9.9 x 10.5 x 14.8 cm
 Regulation Range: +/- 30°
 Weight: 0.87 kg
 Mast Dimensions Range: 250 650 mm
 Material Poliamid with fiberglass + galvanized steel

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

