

Item no.: PA-M5-22HV WIBOX PA M5-22HV - 5 GHz, 22 dBi PtP/Client Antenna





Product Description

Wireless Instruments WiBOX PA M5-22HV - 5 GHz, 22 dBi PtP/Client AntennaWiBOX PA M5-22HV is an dual polarity H&V polarized (MIMO 2x2) planar antenna operating at the frequency range of 5.1 - 5.95 GHz with 22 dBi gain in both polarizations. It was designed for point-to-point (PtP) or point-to-multipoint (PtMP) as the client antenna, where the high-gained antennas are required. WiBOX PA M5-22HV works with WLAN 802.11n/ac systems. It can be installed indoors and outdoors (IP67). The antenna is integrated into the top-quality WiBOX Large system. Features

- 2x 22 dBi gain
 Polarization H&V for the frequency of 5100 5900 MHz
- 2x SMA female connectors
- Big, ergonomic and voluminous WiBOXLarge enclosure for radio equipment installation
 Outdoor waterproof enclosure WiBOXLarge
 Designed for and resistant to any weather conditions

- RJ45 waterproof system
 Grounding system protecting against lightning DC ground

Systems

- WLAN 5 GHz
 WiMAX 5 GHz
 ISM 5725 5875 MHz
 RFiD 5725 5875 MHz

Applications

- System integrationPoint-to-Point connections
- Point-to-Multipoint connections

Electrical Specifications

- Frequency: 5.1 5.9 GHz

- Frequency: 5.1 5.
 Gain: 22 dBi
 VSWR: < 2.00
 Beamwidth: 8°/16°
 Polarization: H&V
- Cross-Polar Isolation •
- Front-to-Back: > 30 dB
 Separation between Connectors: > 35 dB
- Impedance: 50 ohms
 Max Input Power: 50 W
- Lighting Protection: No
 DC Ground: Yes

Mechanic Specifications

- Dimensions: 39.2 x 39.6 x 9.6 cm
 Weight: 3 kg
 Connector: RJ45
 Material: ABS
 Waterproof level: IP67
 Operating temperature from: -40 °C to 80 °C

Mounting Kit

- Dimensions: 9.9 x 10.5 x 14.8 cm
 Regulation Range: +/- 30°
 Weight: 0.87 kg
 Mast Dimensions Range: 250 650 mm
 Material Poliamid with fiberglass + galvanized steel

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

