

Item no.: 398566

DS50U7 - Barebone XPC slim Intel Core i7-10510U 2xSODIMM DDR4 2xM.2 1xSATA

from **861,52 EUR**

Item no.: 398566
shipping weight: 2.90 kg
Manufacturer: Shuttle



 Product Description

Fanless 1.3 litre PC in industrial design with integrated ULV processorThe DS50U series are slim, fanless barebone PCs in a robust metal housing with universal connection options. The soldered Intel Gen12/13 ULV processor offers sufficient performance for the playback of 2160p/60 videos in 4K resolution. Two digital connections for UHD displays and a traditional VGA port are available. Components are easy to install: two DDR5 memory modules, a 2.5" drive and two M.2-2280 SSD cards can be accommodated behind the practical housing cover. A 4G/5G module can also be optionally integrated into the second M.2 slot using the WWN04 adapter kit. Thanks to completely passive cooling, the system is practically maintenance-free, suitable for 24/7 continuous operation and also very economical. It is ideal for professional applications such as digital signage, POS, control, office or as a media PC. Fanless and quietPassive cooling, no fan noiseIdeal for noise-sensitive environmentsLess contamination from dust - therefore virtually maintenance-free 24/7 continuous operationThis device is officially approved for 24-hour continuous operation (24/7). Requirements: - Free air circulation in the area surrounding the PC- Freely accessible ventilation holes on the device.- If a hard drive is installed, the hard drive must be installed on the device. If a hard disk is installed, this must also be approved by the manufacturer for 24/7 operation. HousingSlim PC (nettop) with black steel housingWithout fan, complete with passive coolingThe installation slot for memory modules, 2.5" drive and M.2 cards are easily accessible behind two cover platesDimensions: 20 x 16.5 x 3.95 cm (LWH) = 1.3 litresWeight: 1.6 kg net and 2.3 kg grossTwo openings for Kensington Lock and numerous M3 threaded openings on both sides of the housing. Operating position:1) Vertical: The device is usually operated in an upright position using the supplied stand (DisplayPort connection facing upwards).2) VESA mount: Use the supplied VESA mount to install the device behind a suitable monitor, for example. Operating systemThis barebone system is supplied without an operating system. It is compatible with Windows 10/11 (64-bit) and Linux (64-bit). ProcessorModel: Intel Core i7-1355UCodename: Raptor Lake-U (13. Generation Intel Core)Performance cores (P-cores): 2 cores (4 threads), base/turbo clock: 1.7-5.0 GHzEfficiency cores (E-cores): 8 cores (8 threads), base/turbo clock: 1.2-3.7 GHzSmart cache (L3): 12 MBPower dissipation (PL1 TDP): max. 15 WMaximum junction temperature: 100 °CSystem-on-a-chip architecture (SoC) with integrated memory and graphics controllerBGA1700 housing - soldered directly onto the mainboardManufacturing process: Intel 7 process (improved 10 nm process) Integrated graphicsIntel UHD GraphicsGraphics clock frequency: max. 1300 MHzExecution units (EUs): 96Supports up to three independent displays1) DisplayPort 1.4 supports Ultra HD @ 60 Hz2) HDMI 2.0b supports Ultra HD @ 60 Hz3) D-Sub/VGA supports analogue displays Mainboard / BIOSProprietary mainboard especially for the DS50U seriesSupports resume after power failure [2]Supports Wake on LAN (WOL)Supports power on by RTC alarmSupports booting from M.2 SSD cards and USB devicesAMI BIOS in 32 MByte EEPROM with SPI interfaceSupports hardware monitoring and watchdog functionSupports the Unified Extensible Firmware Interface (UEFI)Supports firmware TPM (fTPM) version 2.0 Power supplyExternal 90 W power supply (fanless)Input: 100-240 V AC, 50/60 Hz, max. 1.6 AOutput: 19 V DC, max. 4.74 A, max. 90 WLength of DC cable: approx. 170 cmLength of AC mains cable: approx. 170 cm (3-pin with C6 cloverleaf and Schuko plug) DC inputDC plug: 5.5 / 2.5 mm (outer/inner diameter)The DC input of the computer supports an external power supply with 12V±5% and 19V±5%. Memory support2x SO-DIMM slot with 262 pinsSupports DDR5-5200 (PC5-41600) SDRAM with 1,1 VAlso supports memory modules with a higher frequency specificationSupports dual-channel modeSupports a maximum of 32 GB per slotTotal capacity maximum 64 GBSupports unbuffered DIMM modules (no ECC or registered)Two thermal pads for the RAM modules are included in the scope of delivery 2,5" drive bay with SATA connectionSupports one Serial ATA hard drive or one SATA SSD drive in 6.35 cm / 2.5" formatDrive height max. 9.5 mmSupports Serial ATA III, 6 Gb/s (600 MB/s) data transfer rateSupports the Unified Extensible Firmware Interface (UEFI)Note: A SATA cable is not required. Two M.2-2280 slots for SSD cardsThis product has two M.2-2280 Key-M slots- M.2 cards with 22 mm width and 80 mm length are supported (type 2280)- One M.2 SSD card with PCIe/NVMe interface is supported- The second M.2 SSD card must have a SATA interface.SSD card must have a SATA interface- the second slot can also be used for the optional WWN04 kit to install a 4G/5G network module.The following configurations are supported: M.2 slot for WLAN cardsSlot: M.2-2230 Type EInterfaces: PCI-Express Gen. 3.0 X1 and USB 2.0The M.2-2230 plug-in cards used must be 22 mm wide and 30 mm long (type 2230)The device has two pre-installed antenna cables.A WLAN expansion card in M.2-2230 format and two WLAN antennas are required for the WLAN function.format and two WLAN antennas are required.Optional Shuttle accessory: WLAN-M1 Sound functionAudio Realtek® ALC888S High-Definition AudioTwo analogue 3.5 mm audio connections on the front: 1) 2-channel line-out (headphones)2) Microphone inputDigital multi-channel audio output via HDMI and DisplayPort Dual network (2.5G + 1G)Two RJ45 network connectionsNetwork chips used:1) left: Intel i219 Ethernet controller supports 1,000 / 100 / 10 MBit/s data transfer rate2) right: Intel i226 Ethernet controller supports 2,500 / 1,000 / 100 MBit/s data transfer rateSupports WAKE ON LAN (WOL)Supports booting from the network via Preboot eXecution Environment (PXE) Ports/buttons on the front4x USB 3.2 Gen 1 (max. 5 Gbit/s, blue)2x USB 3.2 Gen 2 (max. 10 Gbit/s, red)Microphone inputAudio line-out (headphones)On/off buttonPower indicator LED (blue)Hard drive LED (yellow) Rear connectionsDisplayPort 1.4 [3]HDMI 2.0bD-Sub/VGA2x USB 2.0 (black)2x Intel RJ45 network (left: 1 Gbit/s and right: 2.5 Gbit/s)Serial COM port (5V / 12V, switchable: RS232 / RS422 / RS485) [1]DC input for external power supplyFour-pin connector (2.54 mm pitch) for power button, Clear CMOS and 5 V DC [4]2x connectors for external WLAN antennas Always-on jumperIf jumper JP1 is removed (see quick guide), the PC will start unconditionally as soon as the power supply is established. [2]Scope of deliveryMultilingual installation guideTwo metal feet with four M3 x 7 mm screwsVESA bracket for 75/100 mm standard (two metal brackets)Four M3 x 7 mm screws (connects VESA bracket to PC)Four M4 x 10 mm screws (connects VESA bracket to external mounting)Two M3 x 5 mm screws for mounting a 2.5" driveTwo M3 x 5 mm screws for mounting M.2-cards4x thermal pad for cooling optional components:- 2x for M.2SSD card (approx. 70 x 20 x 4 mm)- 2x for RAM module (approx. 50 x 15 x 2 mm and 60 x 20 x 1 mm)Driver DVD for WindowsExternal 90W power supply unit with mains connection cable (with earthing contact) Optional accessories-PCP11:Adapter cable for a second COM port (replaces the VGA port)- CXP01:Adapter cable for an external power button- WLAN-M1:WLAN module (supports WLAN/Bluetooth) with two external antennas and cables- PRM01:2U rack panel for two Shuttle XPC slim- DIR01:DIN rail mounting kit (for 35 mm DIN rails)- WWN04:4G/5G kit with antennas - enables the use of an optional 4G/5G card in the M.2-format and a nano SIM card Environmental parametersPermissible operating temperature range: 0-40 °C [5]Relative humidity, non-condensing: 10-90 % Conformity and certificatesEMI: CE, FCC, BSMI, RCM, VCCI Safety: CB, BSMI, cTUVusOther: RoHS, Energy Star, ErPTThis device is categorised as Class B information technology equipment (ITE) and is primarily intended for use in residential and office environments. The CE mark confirms conformity with the following EU directives:(1) Directive 2014/30/EU on electromagnetic compatibility (EMC)(2) Directive 2014/35/EU on the safety of electrical equipment (LVD)(3) Directive 2009/125/EC on the ecodesign of energy-related products (ErP)Notes:[1] Jumper for COM port configuration:Pin 9 of the two COM ports is a multifunctional connection. The mainboard jumper JP2 can be used to configure whether pin 9 is switched as a "RingIndicator" (RI) or provides an external power supply of 5 V or 12 V. Both COM ports can be configured individually.The COM 1 connection can be set to either RS232, RS422 or RS485 in the BIOS setup.The second COM port (COM 2) only supports RS232 mode. The connection is only available on the mainboard in the standard configuration of this product. To route this interface to the outside as a D-Sub connection, you need the appropriate adapter (e.g. the optional accessory PCP11) and you have to do without the VGA connection.[2] Automatic switch-on after power failure:In the BIOS setup under "Power Management Configuration" there is the function "Power-on after Power Fail", which defines how the PC reacts after a power failure. In principle, however, this function can fail in the event of very short power failures, meaning that this product also has a pure hardware solution. If jumper J9 is removed (see quick guide), the PC will start as soon as the power supply is restored.[3] Convert DisplayPort to HDMI/DVIThe DisplayPort output can be converted to HDMI or DVI using an inexpensive, passive adapter cable. For example:DELOCK 82590: 1m, DisplayPort (male, 20P) to HDMI-A (male, 19P)DELOCK 82435: 5m, DisplayPort (male, 20P) to DVI-D (male., 24P)The integrated graphics function recognises the characteristics of the connected display and outputs the appropriate electrical signal - either DisplayPort (without adapter) or HDMI/DVI (with adapter).Conversely, a monitor with DisplayPort cannot be connected to the HDMI output via a simple, passive adapter.[4] Four-pin connector on the rearThis enables the connection of an external power button.In addition, a 5 V DC voltage is provided for external components and the CMOS memory can be cleared using a jumper (Clear CMOS). A suitable cable is available as optional accessory CXP01.[5] Attention:For high ambient temperatures from 35 °C, it is recommended to use SSDs instead of hard disks.

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

